

COMMENTS:

THE SURVEYOR'S CERTIFICATION SHALL BE SUBSTANTIALLY IN THE FORM SHOWN FOR SURVEYS MADE BY BOTH TRADITIONAL AND GPS SURVEY METHODS. FOR TRADITIONAL ONLY SURVEYS USE MSDD STANDARD C12.02. THE SURVEYOR SHOULD REFER TO AND COMPLY WITH THE CURRENT NCBELS RULES 21 NCAC 56.1600, "STANDARDS OF PRACTICE OF LAND SURVEYING IN NORTH CAROLINA", AND G.S. 47-30 FOR ANY RULE AMENDMENTS. www.ncbels.org

REQUIRED MINIMUM ACCURACY STANDARDS: (21 NCAC 56.1603 & .1605)

HORIZONTAL: "URBAN LAND SURVEYS", CLASS "A" (1:10,000+)

VERTICAL: "URBAN AND SUBURBAN VERTICAL CONTROL SURVEYS", CLASS "A"
(Error not to exceed 0.10 times the square root of the numbers of miles run from reference station).

REFERENCE INFORMATION REQUIRED FOR GPS SURVEYS IN THE CERTIFICATION. (REF, NCBELS BOARD RULE 21 NCAC 56.1607).

- (1) POSITIONAL ACCURACY: _____ (0.07 feet +/- 50PPM or less).
- (2) TYPE OF GPS FIELD PROCEDURE: _____
(STATIC, REAL-TIME KINEMATIC, REAL-TIME KINEMATIC NETWORK, ONLINE POSITION USER SERVICE).
- (3) DATE(S) OF SURVEY: _____
- (4) DATUM / EPOCH: _____
(HORIZONTAL (NAD83/86, NAD83(NSRS2007), etc.; VERTICAL (NAVD88)).
- (5) PUBLISHED / FIXED-CONTROL STATIONS USED: _____
(INCLUDE: STATION NAMES, HORIZONTAL POSITION (NORTHING AND EASTING), ELEVATION, DATUM AND EPOCH).
- (6) GEOID MODEL USED: _____
(GEOID03, GEOID06, GEOID09, etc.).
- (7) COMBINED GRID FACTOR(S): _____
- (8) UNITS: US SURVEY FOOT.

SURVEYOR'S CERTIFICATION

I, _____, CERTIFY THAT THIS PLAT WAS DRAWN UNDER MY SUPERVISION FROM AN ACTUAL FIELD SURVEY PERFORMED UNDER MY SUPERVISION (DEED DESCRIPTION RECORDED IN BOOK _____, PAGE _____, OR FROM BOOKS REFERENCED HEREON); THAT THE BOUNDARIES NOT SURVEYED ARE CLEARLY INDICATED AS DRAWN FROM INFORMATION FOUND IN BOOK _____, PAGE _____, OR AS REFERENCED HEREON; THAT THE RATIO OF PRECISION FOR TRADITIONAL SURVEY METHOD IS 1: _____; THAT THE GLOBAL POSITIONING SYSTEM (GPS) OBSERVATIONS WERE PERFORMED TO THE GEOSPATIAL POSITIONING ACCURACY STANDARDS, PART 2: STANDARDS FOR GEODETIC NETWORKS AT THE CLASS "A" ACCURACY CLASSIFICATION (95% CONFIDENCE) AND THE FOLLOWING INFORMATION WAS USED TO PERFORM THE GPS SURVEY:

POSITION ACCURACY: _____

TYPE OF GPS FIELD PROCEDURE: _____

DATE(S) OF SURVEY: _____

DATUM / EPOCH: _____

PUBLISHED / FIELD CONTROL MONUMENTS USED: _____

GEOID MODEL: _____

COMBINED GRID FACTOR: _____

UNITS: _____

THAT THIS PLAT WAS PREPARED IN ACCORDANCE WITH G.S. 47-30 AS AMENDED.

I FURTHER CERTIFY PURSUANT TO G.S. 47-30 (f) (11) (d). THIS SURVEY IS OF ANOTHER CATEGORY AND IS AN EXEMPTION TO THE DEFINITION OF A SUBDIVISION.

WITNESS MY ORIGINAL SIGNATURE AND SEAL THIS THE _____ DAY OF _____, 20 ____.

SIGNED _____ PROFESSIONAL LAND SURVEYOR NO. L - #####

5 1/2"

3"



PUBLIC WORKS DEPARTMENT
1500 Beatty Street
Greenville, North Carolina 27834

CITY OF GREENVILLE, N.C.

USE WITH THE CITY OF GREENVILLE, N.C. STANDARD SPECIFICATIONS ONLY

www.greenvillenc.gov

No.	Date	Description
1	9/16/11	APPROVAL
Scale:	Sheet #:	Detail #:
not to scale	1 of 1	C12.03

ANNEXATION MAP SURVEYOR'S CERTIFICATION - TRADITIONAL & GPS SURVEY METHODS